



Nayra Uranga, ACCIONA

BUSINESS AS UNUSUAL





GOALS OF THE PROJECT...

- ✓ To develop new construction and retrofitting systems based on Biobased material
- ✓ Main requirements of the CONSTRUCTION systems:








Through the project the partners have maintained a focus of the end goal...

- ✓ Three different systems have been designed with the biomaterials develop inside the project:
 - 1 New Building construction system
 - 2 retrofitting systems: Internal & External.

✓ Starting from.....















1. ISOBIO NEW BUILD CONSTRUCTION SYSTEM

- ✓ Pre-manufactured system
- ✓ Thermally stable during summer, winter or when the temperature outside abruptly changes
- ✓ Highly resistant to mould formation, as they are highly diffusive in the presence of moisture
- ✓ Technical characteristics:
 - Total thickness: 332mm
 - Designed U-Value: 0,179W/m2K







- ✓ New construction system layer by layer...
- 1. Hemp lime exterior render, 15mm
- 2. Hemp ISOBIO panel, 50mm
- 3.1 Wood studs, 50mm
- 3.2 BioFib trio insulation, 50mm
- 4. Airtightness barrier
- 5. OSB3 panel
- **6.1** Wood Studs, 145mm
- 6.2. BioFib trio insulation, 145mm
- **7.** Thermo-compressed straw board, 40mm
- 8. Clay plaster interior render, 25mm





- ✓ Pre-manufacturing process of the new build construction system.
 - Reduce installation time and costs on site.
 - Allow a modular design depending the architectural requirements.

✓ All the layer have be assembly protocol

















✓ Installation of New building system in demo buildings.



















ISOBIO EXTERNAL RETROFITTING SYSTEM

- ✓ Pre-manufactured system
- ✓ Reduce the energy consumption needed for heating or cooling.
- ✓ Protect the building from moisture-based damages and possible outbreaks due to temperature changes.
- ✓ Technical characteristics:
 - Total thickness: 210mm
 - Designed U-Value: W/m2K







- ✓ External retrofitting system layer by layer...
- 1. Hemp lime exterior render, 15mm
- 2. Hemp ISOBIO panel, 50mm
- **3.1** Wood studs, 145mm
- 3.2 BioFib trio insulation, 145mm
- 4. Existing wall

✓ Pre-manufacturing process:












✓ Installation of External retrofitting system in different Demo buildings.












ISOBIO INTERNAL RETROFITTING SYSTEM


- ✓ On site executed system
- ✓ Reduce the energy consumption needed for heating or cooling.
- ✓ The system have been design to reduce the interior dimensions as less as possible
- ✓ Technical characteristics:
 - Total thickness: 90mm
 - Designed U-Value: W/m2K







- ✓ Internal retrofitting system layer by layer...
- 1. Existing wall
- 2. Clay Reinforcement mortar
- 3. Hemp ISOBIO rigid panel, 50mm
- 4. Thermo-compressed straw board, 40mm
- 5. Clay plaster interior render, 25mm







✓ Installation on-site of Internal retrofitting system in different Demo buildings.

















ACHIEVEMENTS

- ✓ Constructive elements (new construction system and retrofitting systems) that can be integrated in the buildings have been designed.
- ✓ Installation capability of the systems have been demonstrated using the demo buildings as a showcase for performance monitoring.
- ✓ The technical viability of using bio-based materials on constructive elements to be applied in different European climates have been demostrated, assuring more comfortable buildings regarding energy efficiency.





Discussion

Thanks for your attention, Any questions?



